



HW OFFSHORE FUEL

Offshore Fuel HW is used on offshore oil rigs to transfer petroleum based products with up to 50% aromatic content. This hose has a high working pressure of 500 psi with antistatic wire and MSHA fire-resistant rated cover. This hose can also be used as Liquid Mud HW and a high pressure tank truck hose.

Performance + Specs

Tube

- Nitrile (NBR) (50% Aromatic content, RMA Class A High Oil Resistance)

Cover

- Chloroprene (CR)
- MSHA Fire-Resistant
- Wrapped Finish
- ARPM Class B (Medium Oil Resistance)

Reinforcement

- Spiral-Plied Fabric
- Double Helix Wire
- Antistatic Wire

Temperature Range

- 35°F / -37°C ~ 200°F / 93°C

Design Factor

- 4:1

Packaging

- Coiled and Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

Continental HW Offshore Fuel Loading 500 psi WP MSHA IC-233/0 Made in Canada

Hw Offshore Fuel

Order Codes: 543-495

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3	76.20	4.02	102.08	400	Black	10.00	254.00	29.00	736.60	500	3.45	3.70	5.51	20479085
4	101.60	5.11	129.81	400	Black	12.00	304.80	29.00	736.60	500	3.45	5.28	7.85	20467632
				400	Black	12.00	304.80	29.00	736.60	500	3.45	5.28	7.85	20479086