



HYDROCARBON DRAIN

Continental Hydrocarbon Drain is offered in two configurations; a 500PSI WP wire-braid and a 300PSI WP hand-built spiral plied construction. The 500PSI WP has a design factor of 10:1 while the 300PSI WP version has a 4:1 design factor. Hydrocarbon Drain is a heavy-duty hose designed for hydrocarbon drain service. It is designed to clean out the hot residue created during steam cleaning and withstand harsh high heat and oil environments.

Performance + Specs

Tube

- Nitrile (NBR)

Cover

- Chloroprene (CR)

Reinforcement

- 500 PSI, 539-819: 1 Layer, Braided, Steel Wire
- 300 PSI, 543-729: Spiral-Plied Steel Wire

Temperature Range

- 25°F / -32°C ~ 350°F / 177°C

Design Factor

- 4:1

Packaging

- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

Continental Hydrocarbon Drain Hose® 300 PSI

Hydrocarbon Drain

Order Codes: 543-729 (Blue - Handbuilt), 539-819

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	1.12	28.45	50	Blue			500	3.45	24.75	36.83	20733235
				50	Blue			500	3.45	0.46	0.68	20177678
3/4	19.05	1.33	33.89	50	Blue	29.00	736.60	300	2.07	0.62	0.92	20254919
				100	Blue	29.00	736.60	300	2.07	0.62	0.92	20264356
1	25.40	1.58	40.24	50	Blue	29.00	736.60	300	2.07	0.77	1.14	20913794
				100	Blue	29.00	736.60	300	2.07	0.77	1.14	20467694
1	25.40	1.42	36.07	50	Blue			500	3.45	0.69	1.03	20221522
1-1/2	38.10	2.27	57.78	100	Blue	29.00	736.60	300	2.07	1.56	2.32	20326679
2	50.80	2.77	70.48	25	Blue	29.00	736.60	300	2.07	1.97	2.93	21064166
				100	Blue	29.00	736.60	300	2.07	1.97	2.93	20276441