



INDUSTRIAL ORS / WET EXHAUST

Suitable for water suction and discharge applications including engine intake, bilge exhaust, holding tank, and scupper lines. Also ideal for industrial water transfer where unique sizing is needed to fit over pipe. 543-193 is oil resistant but does not meet SAE J2006 R2 specifications.

Performance + Specs

Tube

- Nitrile (NBR)
- ARPM Class A (High Oil Resistance)

Cover

- SBR synthetic rubber (wrapped impression)

Reinforcement

- Spiral-Plied Synthetic Fabric
- Wire helix

Temperature Range

- -20°F / -29°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- 1/2" - 5" – 50ft Exact length, Coiled & Poly-Wrapped
- 6" - 8" – 25ft Exact length, Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

CONTINENTAL INDUSTRIAL ORS/WET EXHAUST MADE IN CANADA

Industrial ORS / Wet Exhaust

Order Codes: 543-193 (<6"), 541-193 (>6")

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/2	12.70	0.95	24.06	50	Black	1000	6.89	2.00	50.80	29.00	736.60	250	1.72	0.34	0.51	20142763
5/8	16.05	1.08	27.40	50	Black	800	5.52	2.00	50.80	29.00	736.60	200	1.38	0.41	0.60	20149571
3/4	19.05	1.20	30.40	50	Black	800	5.52	3.00	76.20	29.00	736.60	200	1.38	0.46	0.69	20133706
7/8	22.23	1.32	33.58	50	Black	800	5.52	3.00	76.20	29.00	736.60	200	1.38	0.52	0.77	20142765
1	25.40	1.45	36.74	25	Black	600	4.14	3.00	76.20	29.00	736.60	150	1.03	0.58	0.86	20547851
				50	Black	600	4.14	3.00	76.20	29.00	736.60	150	1.03	0.58	0.86	20129126
1-1/8	28.58	1.57	39.92	50	Black	600	4.14	4.00	101.60	29.00	736.60	150	1.03	0.64	0.95	21141378
				50	Black	600	4.14	4.00	101.60	29.00	736.60	150	1.03	0.64	0.95	20138386
1-1/4	31.75	1.70	43.09	50	Black	600	4.14	4.00	101.60	29.00	736.60	150	1.03	0.69	1.03	20107682
1-3/8	35.00	1.82	46.34	50	Black	500	3.45	4.00	101.60	29.00	736.60	125	0.86	0.75	1.12	20123332
1-1/2	38.10	1.94	49.40	25	Black	400	2.76	4.00	101.60	29.00	736.60	100	0.69	0.80	1.18	20547852
				50	Black	400	2.76	4.00	101.60	29.00	736.60	100	0.69	0.80	1.18	20123383
1-5/8	41.50	2.08	52.84	50	Black	400	2.76	4.00	101.60	29.00	736.60	100	0.69	0.87	1.30	20142751
1-3/4	45.08	2.22	56.42	100	Black	400	2.76	4.00	101.60	29.00	736.60	100	0.69	0.94	1.40	20195030
1-7/8	47.63	2.32	58.97	50	Black	400	2.76	6.00	152.40	29.00	736.60	100	0.69	0.98	1.46	20105482
2	50.80	2.45	62.14	25	Black	300	2.07	6.00	152.40	29.00	736.60	75	0.52	1.04	1.55	20547854
				50	Black	300	2.07	6.00	152.40	29.00	736.60	75	0.52	1.04	1.55	20123384
2-1/8	53.98	2.57	65.32	50	Black	300	2.07	6.00	152.40	29.00	736.60	75	0.52	1.10	1.64	20107683
2-1/4	57.15	2.70	68.49	50	Black	300	2.07	6.00	152.40	29.00	736.60	75	0.52	1.16	1.73	20138387
2-3/8	60.77	2.84	72.11	50	Black	300	2.07	8.00	203.20	29.00	736.60	75	0.52	1.23	1.82	20140304
2-1/2	63.50	3.02	76.61	100	Black	300	2.07	8.00	203.20	29.00	736.60	75	0.52	1.55	2.31	20240565
2-7/8	73.28	3.40	86.39	50	Black	200	1.38	8.00	203.20	29.00	736.60	50	0.34	1.77	2.63	20139655
3	76.20	3.51	89.21	100	Black	200	1.38	10.00	254.00	29.00	736.60	50	0.34	1.76	2.62	20195032
3-1/8	79.40	3.64	92.41	50	Black	200	1.38	10.00	254.00	29.00	736.60	50	0.34	1.83	2.73	20107686
3-1/2	89.92	4.05	102.93	50	Black	200	1.38	10.00	254.00	29.00	736.60	50	0.34	2.05	3.06	20135127
4-1/2	114.30	5.10	129.50	100	Black	120	0.83	14.00	355.60	29.00	736.60	30	0.21	3.46	5.15	20278423
5	127.00	5.60	142.19	50	Black	120	0.83	24.00	609.60	29.00	736.60	30	0.21	3.82	5.68	20274816
6	152.40	6.66	169.20	100	Black	120	0.83	30.00	762.00	29.00	736.60	30	0.21	5.15	7.66	20183338
6-5/8	168.28	7.49	190.19	20	Black	120	0.83	36.00	914.40	29.00	736.60	30	0.21	7.42	11.05	21152634
				25	Black	120	0.83	36.00	914.40	29.00	736.60	30	0.21	7.42	11.05	20834558
				25	Black	120	0.83	36.00	914.40	29.00	736.60	30	0.21	7.42	11.05	20344004
8	203.40	8.87	225.30	100	Black	120	0.83	44.00	1,117.60	29.00	736.60	30	0.21	8.91	13.27	20183339