



INSTA-GRIP™ 250

Continental Insta-Grip™ 250 is for use with push-on fittings at working pressures of 250 psi for industrial service. Nonconductive, minimum electrical resistance greater than one (1) megohm per inch of hose length at 1000 Volts DC.

Performance + Specs

Tube - Nitrile / PVC Blend - ARPM Class A (High Oil Resistance)	Cover - Nitrile / PVC Blend - ARPM Class A (High Oil Resistance)
Reinforcement Spiral Synthetic Yarn	Temperature Range -20°F / -29°C ~ 210°F / 99°C
Design Factor 4:1	Packaging 500ft Reels Maximum 3 pieces, 50ft increments
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	Non Stock / Sizes Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

Continental Insta-Grip™ Non-Conductive 3/4" (19.1mm) 250 PSI WP. Made in USA

Insta-Grip™ 250

Order Codes: 569-043 (Blue), 569-015 (Green), 569-013 (Red), 569-014 (Black), 569-016 (Gray)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/4	6.60	0.51	13.00	250	Green					250	1.72	0.09	0.14	21069975
				250	Red	1000	6.89	3.00	76.20	250	1.72	0.09	0.14	21069971
				500	Black					250	1.72	0.09	0.14	20026001
				500	Gray	1000	6.89	3.00	76.20	250	1.72	0.09	0.13	20160048
				500	Green					250	1.72	0.09	0.14	20026043
				500	Red	1000	6.89	3.00	76.20	250	1.72	0.09	0.14	20025988
3/8	9.70	0.65	16.40	250	Green					250	1.72	0.13	0.19	21070019
				250	Red	1000	6.89	4.50	114.30	250	1.72	0.13	0.19	21069990
				500	Black					250	1.72	0.13	0.19	20026012
				500	Blue	1000	6.89	4.50	114.30	250	1.72	0.13	0.19	20470439
				500	Green					250	1.72	0.13	0.19	20026046
				500	Red	1000	6.89	4.50	114.30	250	1.72	0.13	0.19	20025994
1/2	12.90	0.80	20.20	250	Green					250	1.72	0.17	0.26	21070037
				500	Black	1000	6.89			250	1.72	0.17	0.25	20026030
				500	Blue	1000	6.89	6.00	152.40	250	1.72	0.17	0.26	20470438
				500	Green					250	1.72	0.17	0.26	20026050
				500	Red	1000	6.89	6.00	152.40	250	1.72	0.17	0.26	20025999
5/8	16.00	0.94	23.80	250	Green					250	1.72	0.22	0.33	21070082
				250	Red	1000	6.89	7.50	190.50	250	1.72	0.22	0.33	21070080
				500	Black	1000	6.89	7.50	190.50	250	1.72	0.22	0.33	20026035
3/4	19.10	1.08	27.40	250	Red	1000	6.89	9.00	228.60	250	1.72	0.28	0.42	21070095
				500	Black	1000	6.89	9.00	228.60	250	1.72	0.28	0.41	20026037