

INSTA-GRIP™ TC

For low-pressure hydraulic and pneumatic systems such as shop air systems, general industrial, maintenance and automotive manufacturing applications.

Performance + Specs

Tube - Nitrile / PVC Blend - ARPM Class A (high oil resistance)	Cover - Black Dyed Textile Braid - ARPM Class C (limited oil resistance)
Reinforcement 1 Braid Synthetic Yarn	Temperature Range -40°F / -40°C ~ 210°F / 99°C
Design Factor 4:1	Packaging 500ft reels, maximum 4 pieces, 10ft minimum length
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	Non Stock / Sizes For special production run minimum requirements, Contact Customer Service.

Branding

3/8" 300 PSI WP. Made in USA

Insta-Grip™ TC

Order Codes: 535-230 (Black)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/4	6.40	0.50	12.70	500	Black	1200	8.27	2.50	63.50	300	2.07	0.09	0.13	20022593
5/16	7.90	0.56	14.22	500	Black	1200	8.27	3.00	76.20	300	2.07	0.10	0.15	20022595
3/8	9.50	0.64	16.26	500	Black	1200	8.27	3.00	76.20	300	2.07	0.12	0.18	20022597
1/2	12.70	0.75	19.05	500	Black	1200	8.27	5.00	127.00	300	2.07	0.14	0.22	20022600
5/8	15.90	0.91	23.11	500	Black	1200	8.27	6.00	152.40	300	2.07	0.20	0.30	20022602
3/4	19.10	1.03	26.16	500	Black	1200	8.27	7.00	177.80	300	2.07	0.23	0.34	20022604