



LIGHTWEIGHT VACUUM

Lightweight construction used to exhaust fumes and abrasive dust from woodworking machines, metal, rock, granite and similar processing equipment.

Performance + Specs

Tube

- Chemituf®

Cover

- SBR Corrugated

Reinforcement

- Spiral-Plied Synthetic Fabric
- Wire Helix

Temperature Range

- -25°F / -32°C ~ 180°F / 82°C

Packaging

- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental Vacuum Made in Canada

Lightweight Vacuum

Order Codes: 549-207 (Lightweight)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/4	31.75	1.58	40.23	100	Black	5.00	127.00	29.00	736.60	1	0.01	0.48	0.71	20066720
1-1/2	38.10	1.85	47.03	50	Black	6.00	152.40	29.00	736.60	50	0.34	0.61	0.90	20019375
2	50.80	2.35	59.73	50	Black	8.00	203.20	29.00	736.60	50	0.34	0.78	1.17	20019378
3	76.20	3.36	85.33	50	Black	12.00	304.80	29.00	736.60	50	0.34	1.28	1.90	20019379
5	127.00	5.44	138.16	100	Black	20.00	508.00	29.00	736.60	25	0.17	2.87	4.28	20251783