



LIQUID MUD 500

Powerful, heavy duty discharge hose designed specifically for the transfer of liquid mud at high pressures. High performance: Safely handles working pressures up to 500 psi (549-337) and 300 PSI (549-499) with safety factor in excess of 4:1 Special color coding for safety: Distinctive orange longitudinal stripe reduces the risk of improper application and possible accidents from the use of the wrong hose. All-round compounding: The quality of this hose is further enhanced by the tube and cover compounds; renowned for heat, ozone, weathering and oil resistance.

Performance + Specs

Tube

- NITRILE (NBR)

Cover

- 549-499 SYNTHETIC RUBBER (SBR/NR)
- 549-337 - Chemevic (NBR/SBR/PVC)

Reinforcement

- 549-499 Spiral-Plied Synthenic Fabric
- 549-337 Spiral-plied synthetic fabric with grounding wires

Temperature Range

- 35°F / -37°C ~ 200°F / 93°C

Design Factor

- 4:1

Packaging

- Coiled, wrapped and palletized

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure

Branding

CONTINENTAL LIQUID MUD MADE IN CANADA

Liquid Mud 500

Order Codes: 549-337 (500 PSI)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.79	70.80	400	Black	2000	13.79	500	3.45	1.73	2.57	20637055
3	76.20	3.89	98.92	100	Black	2000	13.79	500	3.45	2.84	4.23	20637056
4	101.60	5.00	127.04	400	Black	2000	13.79	500	3.45	4.13	6.15	20150153
6	152.40	7.08	179.92	200	Black	2000	13.79	500	3.45	6.46	9.62	20667613