

LPG DELIVERY PRO™ CGA TYPE 1 LPG-HOSE

LPG DELIVERY PRO™

LPG Deliver Pro™ is for residential and commercial delivery/transfer of liquid propane gas, LPG dispensing, LPG portable heaters, and LPG and natural gas industrial portable heater applications, and natural gas used for fueling hydraulic fracking equipment only. The hose meets UL21, CSA 8.1 and DOT requirements. Additional applications require prior approval. Not for LPG appliances or other consumer applications.

Performance + Specs

Tube

- Nitrile (NBR)

Cover

- Synthetic Rubber
- Pin-Pricked

Reinforcement

- 4 Layers, Spiral, Textile

Temperature Range

- -40°F / -40°C ~ 180°F / 82°C

Design Factor

- 5:1

Packaging

Continental Industrial CTS Distributor LPG Bulk Packaging:

- 1/2": 500ft Reels
- 3/4": 500ft Reels
- 1": 450ft Reels
- 1-1/4": 400ft /Reels
- 1-1/2": 300ft Reels
- Maximum 3 pieces, 50ft increments

Coupling

- For CTS Distributors, please refer to LPG Delivery Pro™ crimp specs and use ContiTech approved fittings. Premade Factory Assemblies also available.

Branding

1" (25.4mm) LPG Delivery Pro™ CGA Type 1 LPG-Hose Issue No. E- 8167 350 PSI (2.4 MPa) Max WP. Made in U.S.A.

LPG Delivery Pro™

Order Codes: 595-042

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/2	12.90	0.93	23.60	500	Black	350	2.41	0.25	0.37	20640184
3/4	19.30	1.22	31.00	500	Black	350	2.41	0.39	0.58	20640185
1	25.60	1.49	37.80	450	Black	350	2.41	0.51	0.76	20889288
1-1/4	32.00	1.80	45.60	400	Black	350	2.41	0.67	0.99	20942586
1-1/2	38.10	2.04	51.80	300	Black	350	2.41	0.78	1.16	20933077