



LW ARCTIC TANK TRUCK

For transfer of petroleum-based products under suction, low-pressure discharge or gravity flow. Flexibility maintained down to -65°F (-54°C).

Performance + Specs

Tube NITRILE (NBR)	Cover CHLOROPRENE (CR)
Reinforcement Spiral-plied synthetic fabric with double wire hel	Temperature Range -65°F / -54°C ~ 180°F / 82°C
Design Factor 4:1	Packaging 100ft lengths, Coiled & Poly-Wrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	Non Stock / Sizes For special production run minimum requirements, Contact Customer Service.

Branding

Example: ContiTech LW Arctic Tank Truck 150 PSI/10 Bar

LW Arctic Tank Truck

Order Codes: 543-365

Product Numbers																
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.56	65.13	100	Blue	800	5.52	4.00	101.60	29.00	736.60	200	1.38	1.23	1.84	20017813
3	76.20	3.57	90.73	100	Blue	600	4.14	6.00	152.40	29.00	736.60	150	1.03	1.91	2.85	20017814
4	101.60	4.67	118.53	100	Blue	600	4.14	9.00	228.60	29.00	736.60	150	1.03	3.00	4.46	20017815
5	127.00	5.68	144.17	100	Blue	600	4.14	12.00	304.80	29.00	736.60	150	1.03	3.73	5.54	20309270