



MARINE SOFTWALL WET EXHAUST

The Softwall Wet Exhaust Hose is engineered for reliable water discharge in marine environments. Ideal for non-pressurized applications such as engine cooling systems, marine toilets, scuppers, and bilge pump outlets, this hose delivers dependable performance where flexibility and oil resistance matter most. This hose does not meet SAE J2006 R1 specifications.

Performance + Specs

Tube Nitrile Synthetic Rubber ARPM Class A (High Oil Resistance)	Cover Nitrile / PVC Blend (Wrapped Finish)
Reinforcement Spiral-plied Synthetic Fabric	Temperature Range -20°F / -29°C ~ 180°F / 82°C
Design Factor 4:1	Packaging 25ft exact lengths, coiled and polywrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	

Branding

CONTINENTAL INDUSTRIAL ORS/WET EXHAUST MADE IN CANADA

Marine Softwall Wet Exhaust

Order Codes: 543-154 (<6 Inch), 541-154 (8"-10")

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/2	12.70	0.93	23.70	25	Black	1000	6.89	29.00	736.60	250	1.72	0.29	0.43	20123258
3/4	19.05	1.18	30.05	25	Black	800	5.52	29.00	736.60	200	1.38	0.39	0.57	20126043
7/8	22.23	1.31	33.23	25	Black	800	5.52	29.00	736.60	200	1.38	0.44	0.65	20115943
1	25.40	1.43	36.40	25	Black	600	4.14	29.00	736.60	150	1.03	0.49	0.72	20107027
1-1/8	28.58	1.56	39.58	25	Black	600	4.14	29.00	736.60	150	1.03	0.54	0.80	20156178
1-1/4	31.75	1.68	42.75	25	Black	600	4.14	29.00	736.60	150	1.03	0.58	0.87	20113717
1-5/16	33.00	1.73	44.00	25	Black	500	3.45	29.00	736.60	125	0.86	0.60	0.90	20107028
1-3/8	35.00	1.81	46.00	100	Black	500	3.45	29.00	736.60	125	0.86	0.64	0.95	20579574
1-1/2	38.10	1.93	49.10	25	Black	400	2.76	29.00	736.60	100	0.69	0.68	1.02	21052751
				25	Black	400	2.76	29.00	736.60	100	0.69	0.68	1.02	20107029
1-3/4	45.08	2.21	56.08	25	Black	400	2.76	29.00	736.60	100	0.69	0.79	1.18	20108751
1-7/8	47.63	2.31	58.63	25	Black	400	2.76	29.00	736.60	100	0.69	0.83	1.24	20115942
2	50.80	2.50	63.40	25	Black	300	2.07	29.00	736.60	75	0.52	1.03	1.53	20107025
2-1/4	57.15	2.75	69.75	25	Black	300	2.07	29.00	736.60	75	0.52	1.14	1.70	20105483
2-3/8	60.77	2.94	74.77	25	Black	300	2.07	29.00	736.60	75	0.52	1.35	2.01	20105484
2-1/2	63.50	3.05	77.50	25	Black	300	2.07	29.00	736.60	75	0.52	1.40	2.09	20107080
2-3/4	70.10	3.31	84.10	25	Black	300	2.07	29.00	736.60	75	0.52	1.54	2.29	20115944
2-7/8	73.28	3.44	87.28	25	Black	300	2.07	29.00	736.60	75	0.52	1.60	2.38	20107081
3	76.20	3.55	90.20	25	Black	200	1.38	29.00	736.60	50	0.34	1.66	2.47	20105485
3-1/8	79.40	3.68	93.40	25	Black	200	1.38	29.00	736.60	50	0.34	1.72	2.56	20137215
3-1/4	82.80	3.81	96.80	25	Black					50	0.34	1.79	2.66	20137216
3-1/2	89.92	4.09	103.92	25	Black	200	1.38	29.00	736.60	50	0.34	1.93	2.87	20107082
				100	Black	200	1.38			50	0.34	1.93	2.87	21101597
4	101.60	4.55	115.60	25	Black	200	1.38	29.00	736.60	50	0.34	2.16	3.22	20110837
4-1/2	114.30	5.05	128.30	25	Black	120	0.83	29.00	736.60	30	0.21	2.42	3.60	20110838
5	127.00	5.55	141.00	25	Black	120	0.83	29.00	736.60	30	0.21	2.67	3.97	20118697
5-1/2	139.83	6.06	153.83	25	Black	120	0.83	29.00	736.60	30	0.21	2.92	4.35	20137217
6	152.40	6.55	166.40	25	Black	120	0.83	29.00	736.60	30	0.21	3.17	4.72	20114451
6-5/8	168.28	7.37	187.08	25	Black	120	0.83	29.00	736.60	30	0.21	4.76	7.08	20126042
7	177.80	7.61	193.40	25	Black					30	0.21	4.12	6.13	20137218
8	203.40	8.75	222.20	25	Black					30	0.21	5.70	8.48	21136546
					Black					30	0.21	5.70	8.48	20137219
8-5/8	218.44	9.34	237.24	25	Black					30	0.21	6.10	9.07	20107026
10	254.00	10.74	272.80	25	Black					30	0.21	7.05	10.49	20137220
10-3/4	273.69	11.59	294.41	25	Black					30	0.21	8.32	12.38	20137221