



MAXXIM™ PREMIER ULTRA

With redesigned thermoplastic cover for improved flexibility & kink resistance, the newly updated Maxxim Premier Ultra can withstand the continuous demanding application requirements better than ever. The new design still incorporates a Venturi pump in the protected confines of the inner fuel hose coupling to keep the vapor path open in the outer hose. As gasoline flows through the Venturi pump, gasoline accumulating in the bottom loop of the vapor hose is collected and returned to the fuel hose. This updated version is C.A.R.B., EVER, and UL 330 Certified.

Performance + Specs

Tube

- Nitrile (NBR)

Cover

- Nitrile / PVC Blend
- Thermoplastic Outer with textile reinforcement and wire helix

Reinforcement

- One Braid Steel Wire

Temperature Range

- -40°F / -40°C ~ 140°F / 60°C

Packaging

- Coupled lengths only, 6 pieces per box

Coupling

- Available as factory coupled assemblies only

Branding

Not Branded

Maxxim™ Premier Ultra
Order Codes: 532-366

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/4	31.80	0.63	15.90	1	Black	50	0.34	2.50	3.72	21045885
				4	Black	50	0.34	6.20	9.22	21046086
				4	Black	50	0.34	3.10	4.61	21045887
				4.6	Black	50	0.34	6.36	9.47	21046087
				5	Black	50	0.34	3.30	4.91	21045889
				5.6	Black	50	0.34	3.40	5.06	21045980
				6	Black	50	0.34	4.54	6.76	21046713
				6	Black	50	0.34	4.64	6.91	21046716
				6	Black	50	0.34	4.74	7.06	21046748
				6	Black	50	0.34	3.20	4.76	21045888
				6	Black	50	0.34	3.50	5.21	21045981
				6	Black	50	0.34	3.80	5.66	21045984
				6	Black	50	0.34	6.40	9.52	21046088
				6	Black	50	0.34	6.59	9.81	21046114
				6	Black	50	0.34	4.24	6.31	21046135
				6.6	Black	50	0.34	3.60	5.36	21045982
				7	Black	50	0.34	6.80	10.12	21046137
				7	Black	50	0.34	3.70	5.51	21045983
				7.6	Black	50	0.34	7.00	10.42	21046138
				8	Black	50	0.34	4.54	6.75	21046150
				8	Black	50	0.34	7.00	10.42	21046711
				8	Black	50	0.34	3.90	5.81	21045985
				8.6	Black	50	0.34	4.64	6.90	21046714
				8.6	Black	50	0.34	7.17	10.67	21046715
				10	Black	50	0.34	7.40	11.02	21046782
				10	Black	50	0.34	2.10	3.12	21045884
				12	Black	50	0.34	7.80	11.61	21046783
				12	Black	50	0.34	4.71	7.01	21045986