

MIL-PRF-370 TYPE B

This specification covers standard non-collapsible, liquid fuel transfer hose & hose assemblies. MIL-PRF-370L - 2019 SUPERSEDING MIL-PRF-370K - 2017

Performance + Specs

Tube NITRILE (NBR)	Cover Chloroprene (CR)
Reinforcement SPIRAL-PLIED FABRIC; WIRE HELIX	Temperature Range -25°F / -32°C ~ 180°F / 82°C
Design Factor 4:1	Packaging Coiled & Wrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	

Branding

CONTINENTAL CONTITECH ?Q?? CONTRACT# MIL-PRF-370 TYPE B LIQUID FUEL PIN# MADE IN CANADA (Spiral embossed tape) (CONTRACT# & PIN# will only appear upon customer's request

MIL-PRF-370 TYPE B

Order Codes: 543-381

Product Numbers														
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	1.37	34.69		Black	3.50	88.90	29.00	736.60	125	0.86	12.34	18.36	21112004
1	25.40	1.62	41.04	66	Black	4.00	101.60	29.00	736.60	125	0.86	0.82	1.21	21212712