

OFFSHORE FUEL 500

Engineered for the extreme demands of offshore fueling operations, the Offshore Fuel 500 Viton hose delivers reliable performance where safety, chemical resistance, and durability are non-negotiable. Built with a premium black Viton® tube, this hose provides exceptional resistance to a wide range of fuels, including high-aromatic blends and aggressive additives commonly used in offshore environments. Viton’s superior compatibility ensures long service life, reduced permeation, and dependable fluid integrity even under continuous heavy-duty use.

Performance + Specs

Tube Viton	Cover - Chloroprene - ARPM Class A (High Oil Resistance)
Reinforcement Spiral-Plied Synthetic Fabric With Double Wire Helix	Temperature Range -25°F / -32°C ~ 250°F / 121°C
Design Factor 4:1	Packaging Coiled, Wrapped and Palletized
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	

Branding

CONTINENTAL OFFSHORE PETROLEUM TRANSFER WITH FLOSYN 500 PSI WP (RATED FOR 275 PSI WP WHEN CONVEYING CHEMICALS) REFER TO CONTITECH MADE IN CANADA

OFFSHORE FUEL 500

Order Codes: 543-410

Product Numbers										
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3	76.20	3.97	100.80	400	Black	275	1.9	3.70	5.51	21221768
4	101.60	5.16	131.10	400	Black	275	1.9	1.11	1.65	21221765