



OILFIELD FRAC 400 D

A rugged and flexible hose designed to convey crude oil and oil slurry mixtures for Frac tank connections. The Plicord Oilfield Frac Hose has a yellow wear indicator over the fabric reinforcement for optimizing to maximum service life.

Performance + Specs

Tube - Nitrile (NBR) - ARPM Class A (High Oil Resistance)	Cover 543-827: Chemivic - ARPM Class A (High Oil Resistance), Abrasion Resistant 543-710: 100% ARC - Superior Abrasion Resistant, Easy to drag 543-085: Carboxilated Nitrile (XNBR) - ARPM Class A (High Oil Resistance), Superior Abrasion Resistant, Cut & Gouge Resistant
Reinforcement Multiple plies of synthetic fabric	Temperature Range -25°F / -32°C ~ 180°F / 82°C
Design Factor 4:1	Packaging 100ft lengths, Coiled & Poly-Wrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure. 543-710 Plicord® Oilfield Frac hose with ARC cover requires a welded stem/ferrule with fish scale serra	Non Stock / Sizes For special production run minimum requirements, contact Customer Service.

Branding

Continental Oilfield Fracturing Hose

Oilfield FRAC 400 D

Order Codes: 543-827, 543-710

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3	76.20	3.71	94.20	100	Black	1600	11.03	29.00	736.60	400	2.76	2.06	3.06	20118130
3	76.20	3.72	94.60	400	Clear			29.00	736.60	400	2.76	2.08	3.09	20450376
4	101.60	4.78	121.52	100	Black	1600	11.03	29.00	736.60	400	2.76	3.04	4.52	20018362
				400	Black	1600	11.03	29.00	736.60	400	2.76	3.04	4.52	20863695
				400	Black	1600	11.03	29.00	736.60	400	2.76	3.04	4.52	20303585
4	101.60	4.80	121.92	100	Clear	1600	11.03	29.00	736.60	400	2.76	3.06	4.56	20450377
				200	Clear	1600	11.03	29.00	736.60	400	2.76	3.06	4.56	20485255