

Continental 4 SP PACER™ cULus LISTED 559 GASOLINE HOSE MP

PACER™

Pacer™ is for all types of gasoline dispensing applications where flexibility and a lightweight hose is desired. Pacer™ is designed with a spiral textile reinforcement. This hose is UL 330 and CUL approved. Compatible with fuels up to E10 and B5.

Performance + Specs

Tube	Cover
Nitrile (NBR)	Nitrile / PVC Blend
Reinforcement	Temperature Range
Spiral Synthetic Yarn, Static Wire	-40°F / -40°C ~ 140°F / 60°C
Packaging	Coupling
Reels or Coupled Lengths	Available as factory coupled assemblies only
Non Stock / Sizes	
For special production run minimum requirements, Contact Customer Service	

Branding

Continental 4 SP PACER™ UL LISTED 559 GASOLINE HOSE MP

Pacer™

Order Codes: 595-015 (Copper Static Wire), 595-017 (Stainless Steel Static Wire)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.20	1.15	29.20	5	Black	200	1.38	50	0.34	4.00	5.96	20351667
				10	Black	200	1.38	50	0.34	3.34	4.98	20351169
				14	Black	200	1.38	50	0.34	4.66	6.94	20352021
				17	Black	200	1.38	50	0.34	5.65	8.41	20352024
				20	Black	200	1.38	50	0.34	6.64	9.87	20352027
				25	Black	200	1.38	50	0.34	8.28	12.32	20350002
				50	Black	200	1.38	50	0.34	16.50	24.56	20350005
				75	Black	200	1.38	50	0.34	24.73	36.80	20350006
				164	Black	200	1.38	50	0.34	53.96	80.30	20836587
1	25.40	1.48	37.50	500	Black	200	1.38	50	0.34	0.33	0.49	20028829
				10	Black	200	1.38	50	0.34	5.26	7.82	20352431
				12	Black	200	1.38	50	0.34	6.29	9.36	20352433
				14	Black	200	1.38	50	0.34	7.32	10.90	20352417
				17	Black	200	1.38	50	0.34	8.88	13.21	20352418
				20	Black	200	1.38	50	0.34	10.43	15.52	20352419
				25	Black	200	1.38	50	0.34	13.01	19.36	20352080
				50	Black	200	1.38	50	0.34	25.85	38.47	20352081
				450	Black	200	1.38	50	0.34	0.52	0.77	20028867