



PGC PLACEMENT TEXTILE

An economical version of our Allcrete® Textile hose. For use in plaster & grout and shotcrete applications, handling a multitude of materials being pumped to concrete structures, dams, tunnel faces, swimming pools, etc. Meets ASME B30.27-2019. 2:1 WP to burst ratio.

Performance + Specs

Tube

- Chemituf® (Static dissipating), ISO 4649

Cover

- SBR (Wrapped Impression)

Reinforcement

- Spiral-plied High-strength Fabric.

Temperature Range

- -25°F / -32°C ~ 180°F / 82°C

Packaging

- 50ft lengths, Coiled & Poly-Wrapped

Coupling

- Refer to Continental Assembly manual or contact fitting manufacture for proper fitting recommendations and copuling procedures.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

CONTINENTAL PGC CONCRETE ID 1233PSI/85 BAR WP LBS/FT MEETS/EXCEEDS ASME B30.27 MADE IN CANADA

PGC Placement Textile

Order Codes: 549-822

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.61	41.00	50	Black	4932	34.00	1233	8.5	0.64	0.96	20560651
				100	Black	4932	34.00	1233	8.5	0.64	0.96	20727975
1-1/4	31.75	1.91	48.63	50	Black	4932	34.00	1233	8.5	0.86	1.28	20560652
				100	Black	4932	34.00	1233	8.5	0.86	1.28	20763249
1-1/2	38.10	2.16	54.98	50	Black	4932	34.00	1233	8.5	0.99	1.47	20528827
				100	Black	4932	34.00	1233	8.5	0.99	1.47	20763310
2	50.80	2.68	68.16	50	Black	4932	34.00	1233	8.5	1.30	1.93	20528900
				100	Black	4932	34.00	1233	8.5	1.30	1.93	20728506
2-1/2	63.50	3.31	84.10	50	Black	4932	34.00	1233	8.5	1.73	2.58	20528902
3	76.20	3.87	98.36	50	Black	4932	34.00	1233	8.5	2.42	3.61	20528904
3-1/2	89.92	4.43	112.56	50	Black	4932	34.00	1233	8.5	2.87	4.27	20560653