



PROSPECTOR™ FLEX PETRO

For use in tank truck and in-plant operations to transfer gasoline, oil ethanol blends and other petroleum-based products.

Performance + Specs

Tube

- Nitrile (NBR)

Cover

- SBR

Reinforcement

- Multiple Fabric plies with Wire Helix

Temperature Range

- -25°F / -32°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- Coiled and polywrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure

Branding

Prospector™ Flex Petro 150

Prospector™ Flex Petro

Order Codes: 543-266 (Red), 543-309 (Black)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.39	60.66	100	Black	600	4.14	4.00	101.60	29.00	736.60	150	1.03	0.88	1.31	20704228
3	76.20	3.52	89.39	100	Black	600	4.14	6.00	152.40	29.00	736.60	150	1.03	1.76	2.62	20704229
				100	Red			7.00	177.80	29.00	736.60	150	1.03	1.81	2.70	20676272
4	101.60	4.57	115.98	100	Red			10.00	254.00	29.00	736.60	150	1.03	2.62	3.90	20694549