



PROSPECTOR™ PETRO

A flexible and lightweight hose for use in tank truck and drilling operations to transfer diesel, ethanol, gasoline, oil and petroleum-based products. Smooth cover construction for lower drag coefficient and superior abrasion resistance. Up to 50% aromatic content.

Performance + Specs

Tube

- Nitrile (NBR)

Cover

- SBR

Reinforcement

- Spiral-Plied Synthetic Fabric With Double Wire Helix

Temperature Range

- 25°F / -32°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- 100ft lengths, Coiled & Poly-Wrapped

Coupling

- Use Continental ContiTech Insta-lock™ Cam & Groove Fittings.

Branding

CONTINENTAL PROSPECTOR (OIL+GAS LOGO) PETRO 150(1"-5" 150 PSI / 6" 60 PSI) MADE IN CANADA

Prospector™ Petro

Order Codes: 543-214

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	1.94	49.28	100	Black	4.00	101.60	29.00	736.60	150	1.03	0.81	1.21	20476860
2	50.80	2.44	61.97	100	Black	5.00	127.00	29.00	736.60	150	1.03	1.04	1.55	20476861
3	76.20	3.54	89.93	100	Black	9.00	228.60	29.00	736.60	150	1.03	1.91	2.84	20476863
4	101.60	4.57	116.10	100	Black	12.00	304.80	29.00	736.60	150	1.03	2.67	3.97	20476864