



PROSPECTOR™ WATER DISCHARGE

Prospector™ Water Discharge 150 is for use in heavy-duty service for a wide-range of applications.

Performance + Specs

Tube

- SBR

Cover

- SBR

Reinforcement

- Spiral-Plied Fabrics

Temperature Range

- -25°F / -32°C ~ 180°F / 82°C

Design Factor

- 3:1

Packaging

- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

CONTINENTAL PROSPECTOR WATER DISCHARGE 150

Prospector™ Water Discharge

Order Codes: 542-439 (Black)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	0.99	25.25	100	Black	450	3.10	150	1.03	0.20	0.29	20016664
1	25.40	1.24	31.60	100	Black	450	3.10	150	1.03	0.25	0.38	20016665
1-1/4	31.75	1.49	37.95	100	Black	450	3.10	150	1.03	0.32	0.47	20016666
1-1/2	38.10	1.74	44.30	100	Black	450	3.10	150	1.03	0.36	0.54	20016669
1-3/4	45.08	2.06	52.24	100	Black			150	1.03	0.50	0.75	20109557
2	50.80	2.28	57.96	100	Black	450	3.10	150	1.03	0.55	0.82	20016673
2-1/2	63.50	2.78	70.66	100	Black	450	3.10	150	1.03	0.68	1.02	20016676
3	76.20	3.35	85.00	100	Black	450	3.10	150	1.03	1.02	1.52	20016678
3-1/2	89.92	3.89	98.72	50	Black			150	1.03	1.16	1.73	20016681
4	101.60	4.35	110.40	100	Black	450	3.10	150	1.03	1.31	1.95	20016683
				100	Black	450	3.10	150	1.03	1.31	1.95	21082545
5	127.00	5.42	137.64	100	Black	450	3.10	150	1.03	2.01	2.99	20016687
6	152.40	6.42	163.04	100	Black	450	3.10	150	1.03	2.39	3.56	20016689