



PULP & PAPER WASHDOWN

Continental Pulp & Paper Washdown is a heavy-duty water discharge hose for washdown service in pulp and paper mills where kink resistance is of major importance. This hose can be supplied with an integral rubber tapered nozzle.

Performance + Specs

Tube

- EPDM Rubber

Cover

- EPDM Rubber
- Wrapped finish

Reinforcement

- Spiral-plied Synthetic Fabric

Temperature Range

- -25°F / -32°C ~ 200°F / 93°C

Design Factor

- 4:1

Packaging

- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.
Also available with integral tapered nozzle.

Non Stock / Sizes

- Hose: 400' minimum order/400' increments
Hose with tapered nozzle: Two 50' lengths, two 50' length increments

Branding

Continental HD Washdown 300 PSI Max WP

Pulp & Paper Washdown

Order Codes: 542-452 (Black)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	1.31	33.29	50	Black	900	6.21	29.00	736.60	300	2.07	0.50	0.74	20024998
1	25.40	1.62	41.08	50	Black	900	6.21	29.00	736.60	300	2.07	0.70	1.04	20029385
1-1/4	31.75	1.87	47.43	50	Black	900	6.21	29.00	736.60	300	2.07	0.83	1.23	20016713
1-1/2	38.10	2.12	53.78	50	Black	900	6.21	29.00	736.60	300	2.07	0.96	1.43	20100952