



PYROFLEX HOT TAR & ASPHALT

For the transfer of high temperature petroleum-based materials such as Tar and Asphalt. It is suitable for suction and discharge service on tank trucks, tank cars or at bulk stations. Heat resistant tube and Aramid reinforcement. (Hot oils only rated to 200°F/ 93°C)

Performance + Specs

Tube

- Nitrile (NBR)

Cover

- Chloroprene (CR)

Reinforcement

- Spiral-plyed Aramid with Wire Helix

Temperature Range

- 25°F / -32°C ~ 350°F / 177°C

Design Factor

- 4:1

Packaging

- 100ft lengths, Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental Pyroflex® Hot Tar & Asphalt II 150 PSI WP CAUTION: MADE IN CANADA

Pyroflex Hot Tar & Asphalt

Order Codes: 543-118

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	1.33	33.77	100	Black	600	4.14	2.00	50.80	29.00	736.60	150	1.03	0.58	0.87	20017569
1	25.40	1.58	40.15	100	Black	600	4.14	2.50	63.50	29.00	736.60	150	1.03	0.73	1.08	20017572
				400	Black	600	4.14	2.50	63.50	29.00	736.60	150	1.03	0.73	1.08	20685038
1-1/4	31.75	1.83	46.53	100	Black			3.00	76.20	29.00	736.60	150	1.03	0.88	1.31	20439525
1-1/2	38.10	2.08	52.92	100	Black	600	4.14	4.00	101.60	29.00	736.60	150	1.03	1.04	1.54	20017573
2	50.80	2.58	65.62	100	Black	600	4.14	5.00	127.00	29.00	736.60	150	1.03	1.32	1.97	20017574
				300	Black	600	4.14	5.00	127.00	29.00	736.60	150	1.03	1.32	1.97	20241255
2-1/2	63.50	3.09	78.42	100	Black	600	4.14	6.00	152.40	29.00	736.60	150	1.03	1.67	2.48	20046059
3	76.20	3.65	92.82	100	Black	600	4.14	8.00	203.20	29.00	736.60	150	1.03	2.24	3.33	20017578
				400	Black	600	4.14	8.00	203.20	29.00	736.60	150	1.03	2.24	3.33	20315833
4	101.60	4.72	119.95	100	Black	600	4.14	12.00	304.80	29.00	736.60	150	1.03	3.27	4.87	20017580