



PYROFLEX HOT TAR WAND

A high quality wand hose used in asphalt crack filling applicator and dispensing service. Temp max for Oils 200° F.

Performance + Specs

Tube

- Nitrile (NBR)
- ARPM Class A (High Oil Resistance)

Reinforcement

- Spiral-plied (2) Steel Wire

Design Factor

- 4:1

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Cover

- Chloroprene (CR)
- ARPM Class B (Medium Oil Resistance)

Temperature Range

- -25°F / -32°C ~ 350°F / 177°C

Packaging

- 100ft lengths, Coiled & Poly-Wrapped

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental Pyroflex® Hot Tar Wand Hose

Pyroflex Hot Tar Wand

Order Codes: 543-632

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	1.38	35.09	100	Black	1200	8.27	29.00	736.60	300	2.07	0.69	1.03	20017982
				400	Black	1200	8.27	29.00	736.60	300	2.07	0.69	1.03	20017983
1	25.40	1.63	41.44	100	Black	1200	8.27	29.00	736.60	300	2.07	0.85	1.26	20017987
				400	Black	1200	8.27	29.00	736.60	300	2.07	0.85	1.26	20277995
1-1/2	38.10	2.13	54.14	100	Black	1200	8.27	29.00	736.60	300	2.07	1.17	1.74	20156594