



PYROFLEX® II HOT AIR

Pyroflex™ II Hot Air Hose A durable and economical solution for conveying hot air from compressors to storage tanks on bulk dry material carriers. The Pyroflex™ II is engineered for reliable performance in high-temperature pneumatic transfer applications, offering a cost-effective alternative to the Torridair® hose.

Performance + Specs

Tube

- EPDM

Cover

- EPDM

Reinforcement

- Spiral-plied Synthetic Fabric with Wire Helix

Temperature Range

- -20°F / -29°C ~ 325°F / 163°C

Design Factor

- 4:1

Packaging

- 100ft lengths, Coiled & Poly-Wrapped

Coupling

- Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental Pyroflex® II Hot Air

Pyroflex® II Hot Air

Order Codes: 549-394 (2"-6"), 541-394 (8"-12")

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.55	64.86	100	Black	400	2.76	5.00	127.00	29.00	736.60	100	0.69	1.22	1.81	20019669
3	76.20	3.56	90.40	100	Black	400	2.76	7.00	177.80	29.00	736.60	100	0.69	1.88	2.80	20019671
4	101.60	4.61	117.09	100	Black	400	2.76	10.00	254.00	29.00	736.60	100	0.69	2.72	4.05	20019674
6	152.40	6.74	171.20	100	Black	400	2.76	30.00	762.00	29.00	736.60	100	0.69	5.04	7.50	20019675
8	203.40	8.99	228.46	12	Black	300	2.07	48.00	1,219.20	29.00	736.60	75	0.52	9.04	13.45	21134783
10	254.00	11.06	280.98	10	Black	300	2.07	60.00	1,524.00	29.00	736.60	75	0.52	13.12	19.52	21182398