



RED FLEXTRA®

For the transfer of ethanol blends, gasoline and other petroleum-based products under pressure, gravity flow or full-suction where maximum flexibility is needed.

Performance + Specs

Tube	Cover
Nitrile (NBR)	Chloroprene (CR)
Reinforcement	Temperature Range
Spiral-Plied Synthetic Fabric With Double Wire Helix	-30°F / -34°C ~ 180°F / 82°C
Design Factor	Packaging
4:1	100ft lengths, Coiled & Poly-Wrapped
Coupling	Non Stock / Sizes
Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.	For special production run minimum requirements, Contact Customer Service.

Branding

Continental Red Flextra® Made in Canada

Red Flextra®

Order Codes: 543-123 (100 PSI WP), 543-120 (150 PSI WP)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	2.00	50.79	100	Red			3.00	76.20	29.00	736.60	150	1.03	0.91	1.36	20245373
1-1/2	38.10	1.89	48.04	100	Red			3.00	76.20	29.00	736.60	100	0.69	0.72	1.08	20017586
2	50.80	2.39	60.69	100	Red			4.00	101.60	29.00	736.60	100	0.69	0.91	1.36	20017589
				200	Red			4.00	101.60	29.00	736.60	100	0.69	0.91	1.36	20017590
2	50.80	2.52	63.93	100	Red			4.00	101.60	29.00	736.60	150	1.03	1.21	1.80	20017582
2-1/2	63.50	2.89	73.51	100	Red			5.00	127.00	29.00	736.60	100	0.69	1.19	1.76	20017593
				200	Red			5.00	127.00	29.00	736.60	100	0.69	1.19	1.76	20066573
3	76.20	3.44	87.32	100	Red			6.00	152.40	29.00	736.60	100	0.69	1.50	2.24	20017598
3	76.20	3.61	91.62	100	Red			6.00	152.40	29.00	736.60	150	1.03	2.08	3.09	20017583
4	101.60	4.52	114.84	75	Red	400	2.76	9.00	228.60	29.00	736.60	100	0.69	2.37	3.53	20017599
				100	Red	400	2.76	9.00	228.60	29.00	736.60	100	0.69	2.37	3.53	20017600
4	101.60	4.61	117.08	100	Red			9.00	228.60	29.00	736.60	150	1.03	2.76	4.10	20017584