

REDWING BLUE LOW TEMP FUEL OIL

The new and improved Low Temperature Fuel Oil Delivery Hose is for transfer and delivery of fuel oil and petroleum products for home delivery, commercial, and industrial service designed to remain flexible in cold temperatures and provide superior oil resistance. The braided construction reduces kinking and twisting when reeling. The smooth cover has low drag resistance.

Performance + Specs

Tube

- Nitrile (NBR)

Cover

- Nitrile / PVC Blend

Reinforcement

- 2 Layers, Braided Synthetic Yarn
- With Static Wire

Temperature Range

- -50°F / -46°C ~ 140°F / 60°C

Design Factor

- 4:1

Packaging

- Cut lengths

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

Continental 1-1/4" (31.8mm) 2BD. Low Temp Fuel Oil A/S Made in U.S.A.

Redwing Blue Low Temp Fuel Oil

Order Codes: 532-021

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.50	38.10	100	Blue	1000	6.89	250	1.72	0.66	0.99	20865959
				125	Blue	1000	6.89	250	1.72	0.66	0.99	20814591
				150	Blue	1000	6.89	250	1.72	0.64	0.96	20814593
				200	Blue	1000	6.89	250	1.72	0.60	0.89	20973136
				300	Blue	1000	6.89	250	1.72	0.57	0.84	21059186
1-1/4	31.80	1.80	45.72	100	Blue	600	4.14	150	1.03	0.87	1.30	20054898
				125	Blue	600	4.14	150	1.03	0.84	1.25	20031895
				150	Blue	600	4.14	150	1.03	0.82	1.23	20031896
				175	Blue	600	4.14	150	1.03	0.81	1.21	20054428
1-3/8	34.90	1.88	47.75	125	Blue	1000	6.89	250	1.72	0.88	1.32	20031897
				150	Blue	1000	6.89	250	1.72	0.86	1.29	20031898
				175	Blue	1000	6.89	250	1.72	0.85	1.27	20145510
1-1/2	38.10	2.10	53.34	100	Blue	600	4.14	150	1.03	1.08	1.60	20750636
				125	Blue	600	4.14	150	1.03	1.14	1.70	20046244
				150	Blue	600	4.14	150	1.03	1.15	1.71	20031899
				175	Blue	600	4.14	150	1.03	1.07	1.60	20750635