

REDWING® FUEL OIL

Redwing® Fuel Oil is for transfer and delivery of fuel oil and petroleum products for home delivery, commercial and industrial service. Redwing Fuel Oil has two textile braids. The braided construction reduces kinking and twisting when reeling. The smooth cover has low drag resistance.

Performance + Specs

Tube

- Nitrile (NBR)
- ARPM Class A (High Oil Resistance)

Cover

- Red Chemivc synthetic rubber (Nitrile / PVC Blend)
- Smooth finish

Reinforcement

- 2 Layers, Braided Synthetic Yarn
- With Static Wire

Temperature Range

- -40°F / -40°C ~ 140°F / 60°C

Design Factor

- 4:1

Packaging

- Reels, cut lengths and coupled lengths

Coupling

- Coupled assemblies available.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental 1" (25.4mm) 2 BD Redwing Fuel Oil Made in USA

Redwing® Fuel Oil

Order Codes: 532-016

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.50	38.10	100	Red	1000	6.89	250	1.72	0.64	0.95	20021667
1-1/4	31.80	1.80	45.72	100	Red	600	4.14	250	1.72	0.79	1.18	20021681
1-3/8	34.90	1.88	47.75	100	Red	1000	6.89	250	1.72	0.85	1.26	20021708
1-1/2	38.10	2.10	53.34	100	Red	600	4.14	150	1.03	1.07	1.60	20021735