

SANI-WASH™

Continental Sani-Wash™ is used for hot water wash-down and cleanup, up to 210°F (99°C). Use this hose in food processing plants, dairies, packing houses, bottling plants, breweries, canneries, and creameries. The tube is comprised of FDA compliant materials. This product does not contain any phthalates listed in the REACH SVHC list

Performance + Specs

Tube

- Black - EPDM Synthetic Rubber

Cover

- EPDM Synthetic Rubber

Reinforcement

- Spiral Synthetic Yarn

Temperature Range

- 40°F / -40°C ~ 210°F / 99°C

Design Factor

- 4:1

Packaging

- 1/2" - 3/4" - 500ft Reels
- 1" - 450ft Reels
- Max 3 pieces, 50ft Increments

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Downloads

- [Tip 84 Built Washdown Assemblies.pdf](#)
- [Good-Better-Best Washdown Linup.pdf](#)

Branding

Continental Sani-Wash™ 300 PSI WP 3/4" (19.1 mm) Made in USA

Sani-Wash™

Order Codes: 569-020 (Sani-Wash™)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/2	12.70	0.84	21.30	500	White	1200	8.27	300	2.07	0.25	0.38	20070992
5/8	16.00	1.00	25.40	500	White			300	2.07	0.33	0.50	20136571
3/4	19.10	1.17	29.60	500	White	1200	8.27	300	2.07	0.44	0.65	20070993
1	25.40	1.47	37.30	450	White	1200	8.27	300	2.07	0.68	1.01	20070994