

## SCARFING

A heavy duty welding hose designed for scarfing and severe welding applications. The extra thick cover lends protection to the hose in high abuse environments such as steel mills, foundries and industrial plants where hose may encounter high temperatures, sharp edges and abrasion conditions. Hose designed to meet ARPM Grade T materials for all fuel gases, 250 PSI, 4:1 design factor.

### Performance + Specs

|                                                                                                |                                                                                                                                               |
|------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Tube</b> <ul style="list-style-type: none"><li>Chloroprene (CR)</li></ul>                   | <b>Cover</b> <ul style="list-style-type: none"><li>Nitrile / PVC Blend</li></ul>                                                              |
| <b>Reinforcement</b> <ul style="list-style-type: none"><li>Spiral Synthetic Yarn</li></ul>     | <b>Temperature Range</b> <ul style="list-style-type: none"><li>-40°F / -40°C ~ 200°F / 93°C</li></ul>                                         |
| <b>Packaging</b> <ul style="list-style-type: none"><li>1/2" &amp; 3/8" - 500ft Reels</li></ul> | <b>Coupling</b> <ul style="list-style-type: none"><li>Dixon 316 Stainless Steel fittings and Globe ferrules (reference crimp chart)</li></ul> |

### Branding

3/8 (9.5mm) Continental Heavy Duty Fuel Gas 250 PSI Made in USA 1/2 (12.7mm) ContiTech Heavy Duty Oxygen Scarfing Hose 250 PSI Made in USA

**Scarfing**  
**Order Codes:** 569-713 (Red), 569-714

| Product Numbers |         |               |              |             |       |          |          |                 |               |             |
|-----------------|---------|---------------|--------------|-------------|-------|----------|----------|-----------------|---------------|-------------|
| ID (in)         | ID (mm) | Nom. OD (in.) | Nom. OD (mm) | Length (ft) | Color | WP (PSI) | WP (MPa) | Weight (lbs/ft) | Weight (kg/m) | Part Number |
| 3/8             | 9.65    | 0.81          | 20.60        | 500         | Red   | 250      | 1.72     | 0.27            | 0.40          | 20667161    |
| -               | -       | 0.81          | 20.60        |             |       | 250      | 1.72     | 0.27            | 0.40          | 20667059    |