

SINGLE-LINE (GRADE T)

For welding service. Meets ARPM IP-7 and CGA E-1 standards for Grade T welding hose. Non-conductive.

Performance + Specs

Tube

- (CR) Chloroprene

Cover

- Nitrile / PVC Blend
- ARPM Class A (High Oil Resistance)

Reinforcement

- Spiral Synthetic Yarn

Temperature Range

- -40°F / -40°C ~ 120°F / 49°C

Packaging

- - 500ft Reels

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental 1/4" Grade T Fuel Gas Std. Duty Max. WP 200 PSI Meets ARPM IP-7/CGA E-1 Made In USA

Single-Line (Grade T)

Order Codes: 569-619 (Red / Acetylene or other common Welding Fuel Gas), 569-620 (Green / Oxygen), 569-681 (Green Oxygen)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/4	6.60	0.53	13.50	500	Green	200	1.38	0.10	0.16	20683454
				500	Red	200	1.38	0.10	0.16	20027506
5/16	8.10	0.59	15.10	700	Red	200	1.38	0.12	0.18	20309892
3/8	9.50	0.66	16.70	750	Green	200	1.38	0.14	0.21	20027514
3/4	19.10	1.16	29.40	500	Green	200	1.38	0.40	0.59	20777187