



SOFTWALL WET EXHAUST J2006

The Softwall Wet Exhaust Hose is engineered for reliable water discharge in marine environments. Ideal for non-pressurized applications such as engine cooling systems, marine toilets, scuppers, and bilge pump outlets, this hose delivers dependable performance where flexibility and oil resistance matter most. This hose does meet SAE J2006 R1 specifications.

Performance + Specs

Tube

- Synthetic Rubber

Cover

- Nitrile / PVC Blend

Reinforcement

- Spiral-plied Synthetic Fabric

Temperature Range

- -20°F / -29°C ~ 200°F / 93°C

Design Factor

- 4:1

Packaging

- Coiled and polywrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

CONTINENTAL SOFTWALL MARINE WET EXHAUST ID MM SAE J2006 R1 YEAR MADE IN CANADA

Softwall Wet Exhaust J2006

Order Codes: 542-813 (<6 Inch),

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-5/16	33.00	1.73	44.00	50	Black	500	3.45	125	0.86	0.59	0.88	20016985
2-1/8	53.98	2.56	64.98	3	Black	300	2.07	75	0.52	0.91	1.36	20017003
2-3/8	60.77	2.88	73.17	25	Black	300	2.07	75	0.52	1.16	1.72	20864218
3-1/8	79.40	3.66	93.00	50	Black	200	1.38	50	0.34	1.64	2.45	20017025
3-1/2	89.92	4.09	103.92	25	Black	200	1.38	50	0.34	1.91	2.84	20864219
4-1/2	114.30	5.11	129.90	100	Black	120	0.83	50	0.34	2.69	4.01	20017038
5	127.00	5.61	142.60	50	Black	120	0.83	50	0.34	2.97	4.42	20017039
6	152.40	6.68	169.60	50	Black	120	0.83	50	0.34	3.93	5.85	20017043
6-5/8	168.28	7.43	188.68	25	Black			50	0.34	5.21	7.75	20864261