



SPIRAFLEX® AGFLEX

Spiraflex® AgFlex is for water suction and discharge service in construction and septic tank cleaning operations, and is for general industrial and agricultural applications where mild chemical resistance is required.

Performance + Specs

Tube

- PVC Compound

Cover

- PVC Compound

Reinforcement

- Rigid High-Density PVC Helix

Temperature Range

- 0°F / -18°C ~ 158°F / 70°C

Design Factor

- 3:1

Packaging

- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

Not Branded

Spiraflex® Agflex

Order Codes: 586-488

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.23	31.20	100	Clear / White	1.50	38.10	29.00	736.60	60	0.41	0.16	0.24	20013671
1-1/4	31.75	1.52	38.60	100	Clear / White	2.50	63.50	29.00	736.60	50	0.34	0.22	0.33	20013672
1-1/2	38.10	1.78	45.30	100	Clear / White	3.00	76.20	29.00	736.60	50	0.34	0.29	0.43	20013673
2	50.80	2.36	60.00	100	Clear / White	3.20	81.28	29.00	736.60	40	0.28	0.47	0.70	20013674
4	101.60	4.50	114.40	100	Clear / White	10.50	266.70	29.00	736.60	35	0.24	1.34	1.99	20013677