



SPIRAFLEX® AGGIE

Continental Spiraflex® Aggie is general-purpose water suction hose for use in industrial, agriculture and construction applications.

Performance + Specs

Tube

- PVC Compound

Cover

- PVC Compound

Reinforcement

- Rigid High-Density PVC Helix

Temperature Range

- 0°F / -18°C ~ 158°F / 70°C

Design Factor

- 3:1

Packaging

- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Not branded

Spiraflex® Aggie

Order Codes: 586-453

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	0.98	25.00	100	Clear	360	2.48	3.00	76.20	29.00	736.60	120	0.83	0.16	0.24	20013491
1	25.40	1.25	31.80	100	Clear	318	2.19	4.50	114.30	29.00	736.60	106	0.73	0.24	0.36	20013493
1-1/4	31.75	1.53	38.80	100	Clear	297	2.05	5.00	127.00	29.00	736.60	99	0.68	0.32	0.48	20013495
1-1/2	38.10	1.77	44.90	100	Clear	267	1.84	6.00	152.40	29.00	736.60	89	0.61	0.36	0.54	20013497
2	50.80	2.31	58.80	100	Clear	237	1.63	8.00	203.20	29.00	736.60	79	0.54	0.59	0.88	20013500
2-1/2	63.50	2.87	72.90	100	Clear	195	1.34	10.00	254.00	29.00	736.60	65	0.45	0.86	1.28	20013504
3	76.20	3.41	86.60	100	Clear	195	1.34	12.00	304.80	29.00	736.60	65	0.45	1.08	1.60	20013507
4	101.60	4.49	114.00	100	Clear	165	1.14	16.00	406.40	29.00	736.60	55	0.38	1.80	2.68	20013510
6	152.40	6.58	167.20	100	Clear	141	0.97	36.00	914.40	29.00	736.60	47	0.32	3.22	4.79	20013516