



SPIRAFLEX® AIR SEEDER

For dry conveying of seeds and other materials where abrasion is present and service conditions are moderate. Excellent for low-pressure blowing applications.

Performance + Specs

Tube Thermoplastic Urethane	Cover Flexible Vinyl
Reinforcement Rigid Vinyl Helix	Temperature Range 0°F / -18°C ~ 158°F / 70°C
Design Factor 3:1	Packaging Coil wrapped with cardboard and stretch film
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	

Branding

Date Code Only

Spiraflex® Air Seeder

Order Codes: 586-450

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.31	33.20	100	White / Clear	240	1.65	3.00	76.20	29.00	736.60	60	0.41	0.18	0.27	20013448
1-1/4	31.75	1.55	39.30	100	White / Clear			3.00	76.20	29.00	736.60	37	0.26	0.23	0.35	20013449
1-3/4	44.96	2.13	54.20	66	White / Clear			3.00	76.20	29.00	736.60	44	0.3	0.41	0.60	20294126
2-1/2	63.50	3.03	76.90	100	White / Clear	160	1.10	7.00	177.80	29.00	736.60	40	0.28	0.78	1.15	20013452
3	76.20	3.46	87.80	100	White / Clear	140	0.97	8.00	203.20	29.00	736.60	35	0.24	0.93	1.38	20013453
4	101.60	4.71	119.60	100	White / Clear	108	0.74	11.00	279.40	29.00	736.60	27	0.19	1.56	2.33	20013454