



SPIRAFLEX® CABLE GUARD

For use as a protective cover for supply lines. Flame-resistant MSHA approved.

Performance + Specs

Tube

- PVC Compound
- MSHA Certified

Cover

- PVC Compound
- MSHA Certified

Reinforcement

- Rigid High-Density PVC Helix

Temperature Range

- 0°F / -18°C ~ 158°F / 70°C

Packaging

- Continuous one-piece, Coiled & Poly-Wrapped
- Available in 50ft or 100ft lengths.
- Available pre-slit longitudinally for easy installation.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental Cable Guard, USMSHA IC-11/12 Made in USA

Spiraflex® Cable Guard

Order Codes: 586-438

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/4	31.75	1.49	37.80	100	Clear / White	1.77	45.00	0	0	0.16	0.25	20013409
1-1/2	38.10	1.74	44.20	100	Clear / White	2.00	50.80	0	0	0.22	0.33	20013414
2	50.80	2.28	58.00	100	Clear / White	3.00	76.20	0	0	0.23	0.35	20013419
3	76.20	3.37	85.50	100	Clear / White	6.00	152.40	0	0	0.42	0.63	20013425
4	101.60	4.44	112.80	100	Clear / White	9.00	228.60	0	0	0.59	0.88	20013431