



SPIRAFLEX® DUCTING

Versatile enough for use in leaf collection machines, manhole blowers, air conditioning units, and heating applications. As well as for air ducting and pollution control devices. Do not use Spiraflex® Ducting for pressure service.

Performance + Specs

Tube

- PVC Compound

Cover

- PVC Compound

Reinforcement

- Rigid High-Density PVC Helix

Temperature Range

- 0°F / -18°C ~ 150°F / 66°C

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Not Branded

Spiraflex® Ducting

Order Codes: 586-470 (Gray)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.20	30.60	100	Gray			0.11	0.17	21156676
1-1/4	31.75	1.50	38.00	100	Gray			0.16	0.24	21154752
1-1/2	38.10	1.77	44.90	100	Gray			0.22	0.32	20284272
2	50.80	2.27	57.60	100	Gray			0.29	0.43	20013593
3	76.20	3.40	86.30	100	Gray			0.50	0.74	20338906
4	101.60	4.48	113.80	100	Gray			0.61	0.91	20031422
5	127.00	5.43	137.80	100	Gray			0.83	1.24	20706707
6	152.40	6.50	165.20	100	Gray			0.82	1.22	20279072