



SPIRAFLEX® GRASSVAC

For lawn, leaf, mulch and yard waste collection. It is also suitable for dust control, ventilation, and ducting.

Performance + Specs

Tube

- High Molecular Weight PVC

Reinforcement

- Rigid High-Density PVC Helix

Design Factor

- 3:1

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Cover

- High Molecular Weight PVC

Temperature Range

- 0°F / -18°C ~ 158°F / 70°C

Packaging

- 4-6" – 100ft lengths, coiled and poly-wrapped
- 7-8" – 50ft lengths, coiled and poly-wrapped

Non Stock / Sizes

- Available in all black construction.

Branding

Not Branded

Spiraflex® Grassvac

Order Codes: 586-429 (Clear / Black)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
4	101.60	4.46	113.40	100	Clear / Black	45	0.31	4.00	101.60	15.00	381.00	15	0.1	0.72	1.07	20013384
5	127.00	5.49	139.40	100	Clear / Black	45	0.31	7.00	177.80	15.00	381.00	15	0.1	0.99	1.48	20013385
6	152.40	6.56	166.60	100	Clear / Black	30	0.21	7.00	177.80	15.00	381.00	10	0.07	1.43	2.13	20013388
7	177.80	7.63	193.80	100	Clear / Black	30	0.21	9.00	228.60	15.00	381.00	10	0.07	1.68	2.51	20131290
8	203.20	8.64	219.40	50	Clear / Black	30	0.21	9.00	228.60	15.00	381.00	10	0.07	2.14	3.19	20013390