

SPIRAFLEX® LAY FLAT EXTRA LIGHT DUTY - BLUE

Continental Spiraflex® Blue Extra Light Duty is for light-duty water discharge applications in mining, construction, industry, agricultural and marine service.

Performance + Specs

Tube

- PVC

Cover

- PVC

Reinforcement

- Synthetic Fabric

Temperature Range

- 10°F / -23°C ~ 150°F / 66°C

Design Factor

- 3:1

Packaging

- 300ft, One Piece, Coiled & Banded

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental Spiraflex® Blue 2" (50.8 mm) 80 PSI WP (.55 Mpa)

Spiraflex® Lay Flat Extra Light Duty - Blue

Order Codes: 537-564, 537-864

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	1.70	43.20	300	Blue	270	1.86	90	0.62	0.18	0.27	20069152
2	50.80	2.22	56.30	300	Blue	240	1.65	80	0.55	0.23	0.34	20069153
2	50.80	2.21	56.13	328	Blue			80	0.55	0.14	0.21	20852218
2-1/2	63.50	2.78	70.50	300	Blue	165	1.14	55	0.38	0.45	0.67	20069210
2-1/2	63.50	2.68	68.07	328	Blue			55	0.38	0.22	0.33	20852219
3	76.20	3.27	83.00	300	Blue	165	1.14	55	0.38	0.38	0.56	20069213
3	76.20	3.20	81.28	328	Blue			55	0.38	0.27	0.40	20852290
4	101.60	4.30	109.20	300	Blue	150	1.03	50	0.34	0.62	0.92	20069216
4	101.60	4.26	108.20	328	Blue			50	0.34	0.42	0.63	20852291
6	152.40	6.36	161.50	300	Blue	105	0.72	35	0.24	1.08	1.61	20069219
6	152.40	6.26	159.00	164	Blue			35	0.24	0.77	1.15	20852292
8	203.20	8.54	217.00	300	Blue	105	0.72	35	0.24	1.30	1.93	20069222
8	203.20	8.32	211.33	164	Blue			35	0.24	1.17	1.74	20852293