

SPIRAFLEX® LAY FLAT HEAVY DUTY - YELLOW

Continental Spiraflex® Yellow Heavy Duty is for heavy-duty applications in mining, agriculture, construction and marine service. It has limited oil and chemical applications.

Performance + Specs

Tube

- PVC / Nitrile Rubber

Cover

- PVC Compound

Reinforcement

- Synthetic Fabric

Temperature Range

- 10°F / -23°C ~ 150°F / 66°C

Design Factor

- 3:1

Packaging

- 300ft, One Piece, Coiled & Banded

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

Continental Spiraflex® Yellow 2" (50.8 mm), 200 psi (1.38 MPa) Flame-resistant USMSHA 2G-14C/15 Made in USA

Spiraflex® Lay Flat Heavy Duty - Yellow

Order Codes: 537-513

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	1.79	45.50	300	Yellow	600	4.14	200	1.38	0.32	0.48	20012467
2	50.80	2.31	58.80	300	Yellow	600	4.14	200	1.38	0.43	0.65	20012469
2-1/2	63.50	2.86	72.60	300	Yellow	600	4.14	200	1.38	0.66	0.98	20012470
3	76.20	3.38	85.80	300	Yellow	600	4.14	200	1.38	0.78	1.16	20012472
4	101.60	4.40	111.80	300	Yellow	450	3.10	150	1.03	1.04	1.54	20012475
6	152.40	6.44	163.50	300	Yellow	450	3.10	150	1.03	1.59	2.37	20012480