

SPIRAFLEX® LAY FLAT LIGHT DUTY - GRAY

Continental Spiraflex® Gray Light Duty is for light-duty water discharge service.

Performance + Specs

Tube

- PVC

Cover

- PVC

Reinforcement

- Synthetic Fabric

Temperature Range

- -10°F / -23°C ~ 150°F / 66°C

Design Factor

- 3:1

Packaging

- 300ft Continuous one-piece, Coiled & Banded

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental Spiraflex® Gray 2" (53.0 mm) 80 PSI (0.41 Mpa) Made in USA

Spiraflex® Lay Flat Light Duty - Gray

Order Codes: 537-555

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	1.70	43.20	300	Gray	270	1.86	90	0.62	0.18	0.27	20012556
2	50.80	2.22	56.30	300	Gray	240	1.65	80	0.55	0.23	0.35	20012562
2-1/2	63.50	2.78	70.50	300	Gray	180	1.24	60	0.41	0.46	0.68	20012567
3	76.20	3.27	83.00	300	Gray	150	1.03	50	0.34	0.38	0.56	20012572
4	101.60	4.30	109.20	300	Gray	135	0.93	45	0.31	0.62	0.93	20012576
6	152.40	6.36	161.50	300	Gray	105	0.72	35	0.24	1.10	1.63	20012580