

## SPIRAFLEX® LAY FLAT LIGHT / MEDIUM DUTY - GREEN

For medium to light-duty water discharge applications in mining, construction, industry, agricultural and marine service.

### Performance + Specs

#### Tube

- PVC Compound

#### Cover

- PVC Compound

#### Reinforcement

- Synthetic Fabric

#### Temperature Range

- 10°F / -23°C ~ 160°F / 71°C

#### Packaging

- 300ft continuous piece, coiled & branded

#### Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

#### Non Stock / Sizes

- Refer to page 348 of the INH catalog for special production minimum run requirements

### Branding

CONTINENTAL SPIRAFLEX GREEN 1-1/2" ID (38.1 MM) 90 PSI WP (0.62 MPA) MADE IN USA

### Spiraflex® Lay Flat Light / Medium Duty - Green

Order Codes: 537-567

### Product Numbers

| ID (in) | ID (mm) | Nom. OD (in.) | Nom. OD (mm) | Length (ft) | Color | Min. Burst (PSI) | Min. Burst (Mpa) | WP (PSI) | WP (MPa) | Weight (lbs/ft) | Weight (kg/m) | Part Number     |
|---------|---------|---------------|--------------|-------------|-------|------------------|------------------|----------|----------|-----------------|---------------|-----------------|
| 2       | 50.80   | 2.22          | 56.50        | 300         | Green | 237              | 1.63             | 79       | 0.54     | 0.24            | 0.36          | <b>20069281</b> |
| 3       | 76.20   | 3.29          | 83.60        | 300         | Green | 195              | 1.34             | 65       | 0.45     | 0.46            | 0.68          | <b>20069285</b> |
| 4       | 101.60  | 4.31          | 109.50       | 300         | Green | 165              | 1.14             | 55       | 0.38     | 0.66            | 0.98          | <b>20069287</b> |
| 6       | 156.20  | 6.37          | 161.80       | 300         | Green |                  |                  | 50       | 0.34     | 1.14            | 1.70          | <b>20069289</b> |