

SPIRAFLEX® LAY FLAT MEDIUM DUTY - RED

Continental Spiraflex® Medium Duty is for medium-duty discharge applications in mining, construction, industry, agriculture and marine service. Limited oil and chemical application.

Performance + Specs

Tube

- PVC / Nitrile (NBR)

Cover

- PVC (MSHA 2G-14C/16)

Reinforcement

- Spiral Synthetic Yarn
- One Layer Longitudinal Synthetic Yarn

Temperature Range

- 10°F / -23°C ~ 150°F / 66°C

Design Factor

- 3:1

Packaging

- 300ft Continuous one-piece, Coiled & Banded

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental Spiraflex® Red 2" (50.8 mm) 150 PSI WP (1.00 MPa), Flame Resistant, USMSHA 2G-14C/16. Made in USA

Spiraflex® Lay Flat Medium Duty - Red

Order Codes: 537-521

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	1.74	44.10	300	Red	450	3.10	150	1.03	0.23	0.34	20012500
2	50.80	2.27	57.60	300	Red	450	3.10	150	1.03	0.34	0.50	20012501
2-1/2	63.50	2.79	70.80	300	Red	450	3.10	150	1.03	0.49	0.74	20012502
3	76.20	3.29	83.60	300	Red	375	2.59	125	0.86	0.46	0.68	20012503
4	101.60	4.32	109.80	300	Red	300	2.07	100	0.69	0.72	1.07	20012504
6	152.40	6.37	161.80	300	Red	300	2.07	100	0.69	1.23	1.83	20012505