

SPIRAFLEX® LAY FLAT SUPER-DUTY - BLACK

Continental Spiraflex® Black Super Duty is a lay-flat, heavy-duty water discharge and washdown hose that combines the lightweight, compact features of PVC with the durability and abrasion resistance of conventional construction. This hose features a unique one-piece, through-the-weave construction and attains its working pressure from a synthetic woven textile. Resists mildew/rot and requires no drying time. Its excellent durability is derived from a high-tensile rubber compound, which completely encases the jacket. Applications include irrigation, washdown, dewatering, coal preparation and utility plants; gas drilling; jetting and pump discharge; storage tank cleaning and sewer cleaning.

Performance + Specs

Tube

- Nitrile (NBR) / PVC
- Both tube and cover are simultaneously extruded to obtain maximum bending

Cover

- Nitrile (NBR) / PVC

Reinforcement

- Through-The-Weave Fabric

Temperature Range

- -36°F / -38°C ~ 178°F / 81°C

Design Factor

- 3:1

Packaging

- Coiled

Coupling

- Contact your Continental representative for special production run minimum requirements.

Branding

Not Branded

Spiraflex® Lay Flat Super-Duty - Black

Order Codes: 537-805 (Black)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	1.58	40.13	200	Black			300	2.07	0.26	0.39	20466096
2-1/2	50.80	2.58	65.53	100	Black			250	1.72	1.30	1.93	20466020
3	76.20	3.10	78.74	100	Black	690	4.76	230	1.59	1.30	1.93	20466098
4	101.60	4.10	104.14	100	Black	600	4.14	200	1.38	1.30	1.93	20466047
6	152.40	6.13	155.70	100	Black	450	3.10	150	1.03	1.30	1.93	20466364
8	203.20	8.16	207.26	100	Black	450	3.10	150	1.03	1.30	1.93	20466752