



SPIRAFLEX® MULCH BLOWER

For dry conveying of mulch and other materials where abrasion is present and service conditions are moderate. Excellent for low-pressure blowing applications.

Performance + Specs

Tube

- PVC Compound

Cover

- PVC Compound

Reinforcement

- Rigid High-Density PVC Helix

Temperature Range

- -18°F / -28°C ~ 158°F / 70°C

Design Factor

- 3:1

Packaging

- 50ft / 100ft Coils.
- Wrapped with clear stretch film

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

Not Branded

Spiraflex® Mulch Blower

Order Codes: 586-479 (Clear / Black)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
4	101.60	4.46	113.20	100	Clear / Black	60	0.41	6.00	152.40	18.00	457.20	15	0.1	0.99	1.48	20013644
5	127.00	5.61	142.40	100	Clear / Black	60	0.41	9.00	228.60	15.00	381.00	15	0.1	1.49	2.22	20024982