



SPIRAFLEX® ROCK DUST SW

The Spiraflex® Rock Dust hose is a lightweight, flexible alternative to the rubber hose for handling rock dusting in underground coal mines.

Performance + Specs

Tube

- PVC

Cover

- PVC Compound
- MSHA Certified 2G-1C-14C/17

Reinforcement

- Rigid High-Density PVC Helix

Temperature Range

- 0°F / -18°C ~ 158°F / 70°C

Design Factor

- 3:1

Packaging

- 100ft, Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

Rock Dust USMSHA 2G-1C-14C/17 Made in USA Continental

Spiraflex® Rock Dust SW

Order Codes: 586-427 (Static Wire)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.36	60.00	100	Green	120	0.83	6.00	152.40	29.00	736.60	30	0.21	0.70	1.04	20013361
2-1/2	63.50	2.93	74.50	100	Green	120	0.83	7.00	177.80	29.00	736.60	30	0.21	1.03	1.53	20013363