



SPIRAFLEX® VACUUM

Spiraflex® Vacuum hose is for dust collection and exhaust transmission where airborne pollutants, fumes and odors are a major problem.

Performance + Specs

Tube

- PVC Compound

Cover

- PVC Compound

Reinforcement

- Rigid High-Density PVC Helix

Temperature Range

- 0°F / -18°C ~ 158°F / 70°C

Design Factor

- 3:1

Packaging

1"-4" – 100ft lengths, Coiled & Poly-Wrapped

5"-6" – 30ft lengths, Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Not Branded

Spiraflex® Vacuum

Order Codes: 586-403

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.21	30.80	100	White	148	1.02	3.00	76.20	29.00	736.60	37	0.26	0.12	0.18	20013089
1-1/4	31.75	1.54	39.20	100	White	148	1.02	4.00	101.60	29.00	736.60	37	0.26	0.22	0.33	20013090
1-1/2	38.10	1.80	45.70	100	White	136	0.94	4.00	101.60	29.00	736.60	34	0.23	0.28	0.41	20013092
2	50.80	2.36	60.00	100	White	120	0.83	6.00	152.40	29.00	736.60	30	0.21	0.42	0.63	20013094
2-1/2	63.50	2.89	73.50	100	White	120	0.83	7.00	177.80	29.00	736.60	30	0.21	0.59	0.87	20013095
3	76.20	3.43	87.20	100	White	120	0.83	8.00	203.20	29.00	736.60	30	0.21	0.78	1.16	20013096
4	101.60	4.47	113.60	100	White	108	0.74	14.00	355.60	15.00	381.00	27	0.19	1.01	1.51	20013097
6	152.40	6.59	167.50	20	White	80	0.55	25.00	635.00	10.00	254.00	20	0.14	2.17	3.23	20013099