



SPIRAFLEX® VAPOR RECOVERY

Continental SpiraFlex® Vapor Recovery is for the recovery of gasoline vapors in tank truck loading at bulk terminals and in tank truck unloading at service stations.

Performance + Specs

Tube

- Thermoplastic Polyurethane

Cover

- Thermoplastic Polyurethane

Reinforcement

- Rigid High-Density PVC Helix
- with Static Wire

Temperature Range

- 30°F / -34°C ~ 158°F / 70°C

Design Factor

- 3:1

Packaging

- 100ft lengths, Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Not Branded

Spiraflex® Vapor Recovery

Order Codes: 586-468 (Static Wire)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.47	62.80	100	Red / Clear	120	0.83	3.00	76.20	29.00	736.60	30	0.21	0.60	0.90	20013586
3	76.20	3.48	88.40	100	Red / Clear	80	0.55	4.00	101.60	29.00	736.60	20	0.14	0.81	1.21	20013587
4	101.60	4.53	115.00	100	Red / Clear	60	0.41	7.00	177.80	29.00	736.60	15	0.1	0.98	1.46	20013588