



STEAM 250

Continental Steel Steam 250 has a rugged construction used for all-around steam service in chemical plants, refineries, shipyards and demanding industrial service. It is recommended for cleaning, thawing, blowout service, steam pumps, hoists and other applications involving steam.

Performance + Specs

Tube

- EPDM Rubber

Cover

- Black or Red EPDM Rubber
- Wrapped Finish & Pin-pricked

Reinforcement

- Spiral-Plied Steel Wire

Temperature Range

- 0°F / -18°C ~ 406°F / 208°C

Design Factor

- 10:1

Packaging

- Coiled and Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service

Branding

Continental Steel Steam 250 PSI. Drain After Use

Steam 250

Order Codes: 541-060 (2-1/2" to 3" ID - Black), 549-060 (Black < 3"), 549-061 (Red < 3"), 541-061 (Red 3")

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/2	12.70	0.97	24.74	50	Black			250	1.72	0.34	0.50	20019131
				50	Red			250	1.72	0.34	0.51	20019161
				100	Black			250	1.72	0.34	0.50	20019132
				100	Red			250	1.72	0.34	0.51	20019162
3/4	19.05	1.27	32.29	50	Black			250	1.72	0.50	0.74	20019136
				50	Red			250	1.72	0.51	0.76	20019167
				100	Black			250	1.72	0.50	0.74	20019137
				100	Red			250	1.72	0.51	0.76	20019168
				200	Red			250	1.72	0.51	0.76	20019169
1	25.40	1.52	38.64	50	Black			250	1.72	0.62	0.92	20019140
				50	Red			250	1.72	0.64	0.94	20019173
				100	Black			250	1.72	0.62	0.92	20019141
				100	Red			250	1.72	0.64	0.94	20019174
1-1/4	31.75	1.82	46.19	2	Black			250	1.72	163.43	243.21	20419013
				50	Red			250	1.72	0.86	1.28	20019177
1-1/2	38.10	2.12	53.74	50	Black			250	1.72	1.05	1.57	20019147
				50	Red			250	1.72	1.09	1.62	20019179
				100	Black			250	1.72	1.05	1.57	20019148
				100	Red			250	1.72	1.09	1.62	20019180
1-3/4	45.08	2.58	65.56	100	Red			250	1.72	1.76	2.62	20149352
2	50.80	2.81	71.28	50	Black			250	1.72	1.89	2.81	20019151
				50	Red			250	1.72	1.94	2.89	20019183
				100	Red			250	1.72	1.94	2.89	20019184
				400	Black			250	1.72	1.89	2.81	20019154
2-1/2	63.50	3.31	83.98	50	Black			250	1.72	2.35	3.50	20019155
				100	Black	29.00	736.60	250	1.72	2.36	3.50	20703026
				400	Red			250	1.72	2.42	3.60	20019186
3	76.20	3.81	96.68	100	Black	29.00	736.60	250	1.72	2.76	4.11	20688928
				100	Red			250	1.72	2.83	4.21	20019187
				400	Black			250	1.72	2.76	4.10	20019158