



SUPER ROCK DRILL HT

Super Rock Drill HT is an extra heavy-duty, high-pressure hose for pneumatic service in mining, construction and industrial service where working conditions are especially severe. Ozone resistance for outdoor service. Special compound for high temperature application with ARPM Class B oil resistance.

Performance + Specs

Tube

- Chlorinated Polyethylene (CPE)
- ARPM Class B (Medium Oil Resistance)

Cover

- EPDM Rubber (Wrapped Finish)

Reinforcement

- Spiral-Plied Steel Wire

Temperature Range

- -30°F / -34°C ~ 275°F / 135°C

Design Factor

- 4:1

Packaging

- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

Continental Super Rock Drill HT 600 PSI WP Made in Canada

Super Rock Drill HT

Order Codes: 549-078 (Yellow)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.76	70.08	100	Yellow	2000	13.79	600	4.14	1.85	2.75	21050109
				400	Yellow	2000	13.79	600	4.14	1.85	2.75	21087204
3	76.20	3.85	97.88	100	Yellow	2000	13.79	600	4.14	3.02	4.49	21050240