



SUPER ROCK DRILL

Continental Super Rock Drill – Built for the Toughest Jobs in Mining and Construction. When the environment is extreme and the pressure is high, the Continental Super Rock Drill hose stands up to the challenge. This extra heavy-duty, high-pressure hose is purpose-built for pneumatic service in mining, construction, and industrial operations where working conditions are especially severe. This hose is MSHA-approved and engineered for long-lasting performance. It delivers exceptional strength and flexibility. Whether you're powering rock drills, jackhammers, or other pneumatic tools, the Super Rock Drill hose is your go-to solution for maximum durability, safety, and performance in the most demanding environments

Performance + Specs

Tube

- NITRILE (NBR)
- ARPM Class A (High Oil Resistance)

Cover

- Nitrile / PVC Blend
- ARPM Class A (High Oil Resistance)
- MSHA

Reinforcement

- Spiral-Plied Steel Wire

Temperature Range

- -40°F / -40°C ~ 220°F / 104°C

Design Factor

- 4:1

Packaging

- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

Continental Super Rock Drill ORS 500 PSI WP

Super Rock Drill

Order Codes: 541-258 4", 549-258 2"-4"

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.84	72.08	100	Yellow	2000	13.79	500	3.45	2.13	3.16	20236815
				400	Yellow			500	3.45	2.13	3.16	20019472
3	76.20	3.98	101.08	100	Yellow	2000	13.79	500	3.45	3.50	5.21	20019475
4	101.60	4.98	126.48	100	Yellow	1600	11.03	400	2.76	4.58	6.82	20216924