

## SURELINE™

Sureline™ is for a wide range of industrial, construction, and agricultural water discharge applications in which a general service water hose is needed.

### Performance + Specs

#### Tube

- EPDM Rubber

#### Cover

- EPDM Rubber

#### Reinforcement

- Spiral Synthetic Yarn

#### Temperature Range

- -40°F / -40°C ~ 210°F / 99°C

#### Design Factor

- 3:1

#### Packaging

- 3/16" to 3/4" – 500ft Reels
- 1" – 450ft Reels
- 1-1/4" – 400ft Reels
- 1-1/2" – 300ft Reels
- Maximum 3 pieces, 50ft increments

#### Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

#### Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

### Branding

Continental 1/2" Sureline™ 150 PSI WP

#### Sureline™

Order Codes: 569-048 (Red), 569-049 (Black)

### Product Numbers

| ID (in) | ID (mm) | Nom. OD (in.) | Nom. OD (mm) | Length (ft) | Color | Min. Burst (PSI) | Min. Burst (Mpa) | WP (PSI) | WP (MPa) | Weight (lbs/ft) | Weight (kg/m) | Part Number |
|---------|---------|---------------|--------------|-------------|-------|------------------|------------------|----------|----------|-----------------|---------------|-------------|
| 1/4     | 6.35    | 0.48          | 12.19        | 500         | Black |                  |                  | 150      | 1.03     | 0.09            | 0.14          | 20026458    |
| 1/4     | 6.40    | 0.49          | 12.40        | 500         | Red   | 450              | 3.10             | 150      | 1.03     | 0.09            | 0.13          | 20026443    |
| 3/8     | 9.50    | 0.65          | 16.60        | 500         | Black |                  |                  | 150      | 1.03     | 0.15            | 0.22          | 20026459    |
| 13/32   | 9.80    | 0.65          | 16.60        | 500         | Red   | 450              | 3.10             | 150      | 1.03     | 0.14            | 0.21          | 20026444    |
| 1/2     | 12.70   | 0.79          | 20.00        | 500         | Black |                  |                  | 150      | 1.03     | 0.20            | 0.29          | 20026465    |
|         |         |               |              | 500         | Red   | 450              | 3.10             | 150      | 1.03     | 0.20            | 0.29          | 20026447    |
| 5/8     | 15.70   | 0.93          | 23.50        | 500         | Red   | 450              | 3.10             | 150      | 1.03     | 0.27            | 0.40          | 20026448    |
| 5/8     | 16.00   | 0.93          | 23.62        | 500         | Black |                  |                  | 150      | 1.03     | 0.27            | 0.40          | 20026474    |
| 3/4     | 19.05   | 1.08          | 27.50        | 500         | Black |                  |                  | 150      | 1.03     | 0.34            | 0.51          | 20026485    |
| 3/4     | 19.10   | 1.08          | 27.50        | 500         | Red   | 450              | 3.10             | 150      | 1.03     | 0.34            | 0.51          | 20026451    |
| 1       | 25.40   | 1.39          | 35.40        | 450         | Black |                  |                  | 150      | 1.03     | 0.54            | 0.80          | 20026501    |
|         |         |               |              | 450         | Red   | 450              | 3.10             | 150      | 1.03     | 0.53            | 0.79          | 20026454    |
| 1-1/4   | 31.75   | 1.63          | 41.40        | 400         | Black |                  |                  | 150      | 1.03     | 0.62            | 0.93          | 20026508    |
| 1-1/2   | 38.10   | 1.88          | 47.80        | 300         | Black |                  |                  | 150      | 1.03     | 0.74            | 1.10          | 20026512    |
|         |         |               |              | 300         | Red   | 450              | 3.10             | 150      | 1.03     | 0.74            | 1.10          | 20026456    |